

R.205 & R.205SS



Stainless
Steel



Steel



Classe II



AN EXCELLENT PARTNER FOR YOUR BACK AND YOUR HEALTH

Discover our range of **R.205** handling carts, whether it's the R.205 SS in Stainless Steel or the standard R.205, they are designed to meet various professional needs. The R.205 SS in Stainless Steel is specially designed for demanding environments such as the food industry and the pharmaceutical industry. It can handle loads of up to 205 kg, with a maximum lifting height of 239 cm. Possibly equipped with interchangeable stainless steel electrical tools, it offers great versatility. Its safety features, including overload protection, a safety clutch, and soft start, ensure secure handling.

The standard R.205 is a versatile lifting trolley, ideal for moving, lifting, and flipping various loads. It is suitable for the needs of large industries and 24/7 continuous work environments. With multiple safety features and interchangeable tools, it offers convenience and reliability.

The R.205 is delivered with AGM batteries (24 V ; 9 Ah) as standard.



Lift



Move

Features

DESCRIPTION

CMU	205 Kg (S/M) - 180 Kg (L)	
Material	Steel	Stainless Steel
Command type	Remote control	
Battery indicator	On the remote control unit	
Battery type	4 AGM (Tot : 24 V - 18 Ah)	
Charger	External - 230 V - 50/60 Hz	
Number of cycles	80 to 150 cycles	
Recharge time	15 hours (100%)	

MADE IN FRANCE

Contact us :
02 28 21 73 95
info@reglift.fr

Visit our website:
www.reglift.com

 REGLIFT
ZAC La Belle Etoile - 19, rue Saturne
44119 Grandchamp-des-Fontaines



General view


Material

- Steel: IP44
- Stainless steel: IP65

Tool holder

- Home a wide range of manual and power tools
- Quick change system
- Automatic level option
- Position encoder

Braking system



- Central braking

Wheels



- Fixed and free wheels at the front and the rear
- ESD

Variable mast sizes

- L
 - Mast size: 2390 mm
 - Elevation stroke: 2000 mm
- M
 - Mast size: 1940 mm
 - Elevation stroke: 1560 mm
- S
 - Mast size: 1560 mm
 - Elevation stroke: 1180 mm

Handle

- Ergonomic handle: Ergo Control
- Fixed or detachable remote control
- 8 different configurations

Battery options

- Interchangeable batteries
- Lithium battery
- Charger storage case

Legs


- 2 leg configurations
- Different lengths and widths available
- Widening the footings



Examples of tools




Double boom




Jib crane



Platform with rollers



Electric core gripper



Electric rotation clamp



Contact us :
02 28 21 73 95
info@reglift.fr

Visit our website:
www.reglift.com

REGLIFT
ZAC La Belle Etoile - 19, rue Saturne
44119 Grandchamp-des-Fontaines